

## GAS SUPPLY PANELS

### LHPI 800P

#### HIGH PURITY SEMI-AUTOMATIC SWITCHOVER SUPPLY PANEL

The LHPI 800P is a semi-automatic high purity switchover prevents downtime by automatically switching gas supply panel from the primary cylinder bank to the reserve cylinder bank. The user resets the primary bank by turning the knob. Outlet pressure is factory pre-set.

#### APPLICATIONS:

- Laboratory pressure control;
- Research sample systems gases;
- Component testing;
- Petrochemical industry;
- Emission monitoring systems;
- Controlled atmosphere;
- Service & test equipment.

#### FEATURES:

- Recommended for non-corrosive gases purity levels up to grade 6.0 (99.9999);
- Wall mounting panel and brackets included;
- Ready to install wall mounting panel;
- Metal steel diaphragm eliminates contamination from diffusion or outgassing;
- Purge function and diaphragm shut-off valves for the best results;
- Possible to connect 2 gas cylinders or gas cylinder and a gas for purging operation;
- LHPI 800PC - chrome plated body, bonnet and fittings;
- LHPI 800PS - 316L stainless steel body, bonnet and fittings;
- 1x10<sup>-9</sup> mbar l/s He inboard helium leak rate to maintain gas purity levels;
- Inlet / outlet - 1/4" FNPT;
- Maximum inlet pressure 300 bar (4350 psig);
- Tested for use with oxygen.

#### MATERIALS

<b>Body, bonnet</b>	316L stainless steel barstock LHPI 800PS or chrome plated brass barstock LHPI 800PC
<b>Diaphragm (regulator)</b>	Hastelloy® * C276
<b>Diaphragm (valve)</b>	Elgiloy® **
<b>Nozzle</b>	316L stainless steel
<b>Seat</b>	PEEK
<b>Seals O-ring</b>	Viton® *** (FKM)
<b>Filter</b>	SS 316L
<b>Adjusting Knob</b>	ABS plastic


\* Hastelloy® is a registered trademark name of Haynes International, Inc


\*\* Elgiloy® a registered trademark of Elgiloy Specialty Metals

\*\*\* Viton® is a registered trademark of The Chemours Company

#### TECHNICAL DATA


<b>Panel type</b>	Semi-automatic switchover supply panel
<b>Regulator type</b>	Single stage
<b>Purity</b>	Up to 6.0
<b>Inlet pressure</b>	Max. 300 bar (4350 psi)
<b>Outlet pressure</b>	2/4/10/20 bar (29/58/145/290 psi)
<b>Purge function</b>	Yes
<b>Oxygen use</b>	Suitable





## SPECIFICATION

Inlet / outlet ports	1/4" NPT-F
Weight	4,8 kg
Temperature range	-30°C to +74°C



## RELATED OPTIONS

- HAS - 2 - two connection
- 4 - two connection
- 6 - two connection

## EXTENSIONS

